



Calibration complies with ISO/IEC 17025, ANSI/NCSL Z540-1, and 9001

VIE



Cert. No.: 4227-8714952

Certificate No. 1750.01 Traceable® Certificate of Calibration for Refrigerator/Freezer Thermometer

Manufactured for and distributed by: Fisher Scientific, 300 Industry Drive, Pittsburgh, PA 15275-1001 **Instrument Identification**:

Model Numbers: 06-664-23, 11705853 S/N: 170538312 Manufacturer: Control Company

Standards/Equipment:

Serial Number	<u>Due Date</u>	NIST Traceable Reference
A4529U		
A17118	3/27/18	1000406562
128	3/18/18	6-B1I0Q-40-1
93139		
A17118	3/27/18	1000406562
3039	3/18/18	6-B1I0Q-20-1
	A45240 A17118 128 93139 A17118	A45240 A17118 3/27/18 128 3/18/18 93139 A17118 3/27/18

Certificate Information:

Technician: 104

Procedure: CAL-03

AL-03 Cal Date: 7/24/17

Due Date: 7/24/19

Test Conditions:

24.3°C

69.0 %RH 1015 mBar

Calibration Data: (New Instrument)

Unit(s)	Nominal	As Found	In Tol	Nominal	As Left	In Tol	Min	Max	±U	TUR
°C Probe		N.A.		0.000	-0.2	Y	-0.5	0.5	0.059	>4:1
°C Probe		N.A.		50.000	50.0	Υ	49.5	50.5	0.059	>4:1

This Instrument was calibrated using Instruments Traceable to National Institute of Standards and Technology.

A Test Uncertainty Ratio of at least 4:1 is maintained unless otherwise stated and is calculated using the expanded measurement uncertainty. Uncertainty evaluation includes the instrument under test and is calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM). The uncertainty represents an expanded uncertainty using a coverage factor k=2 to approximate a 95% confidence level. In tolerance conditions are based on test results falling within specified limits with no reduction by the uncertainty of the measurement. The results contained herein relate only to the item calibrated. This certificate shall not be reproduced except in full, without written approval of Control Company.

Nominal=Standard's Reading; As Left=Instrument's Reading; In Tol=In Tolerance; Min/Max=Acceptance Range; ±U=Expanded Measurement Uncertainty; TUR=Test Uncertainty Ratio; Accuracy=±(Max-Min)/2; Min = As Left Nominal(Rounded) - Tolerance; Max = As Left Nominal(Rounded) + Tolerance; Date=MM/DD/YY

This certificate indicates calibration for external sensor only.

Micol Rodriguez, Quality Manager

Aaron Judice, Technical Manager

Maintaining Accuracy:

In our opinion once calibrated your Refrigerator/Freezer Thermometer should maintain its accuracy. There is no exact way to determine how long calibration will be maintained. Refrigerator/Freezer Thermometers change little, if any at all, but can be affected by aging, temperature, shock, and contamination.

Recalibration:

For factory calibration and re-certification traceable to National Institute of Standards and Technology contact Control Company.

CONTROL COMPANY 12554 Galveston RD Suite B230 Webster TX USA 77598
Phone 281 482-1714 Fax 281 482-9448 service@control3.com www.control3.com

Control Company is an ISO/IEC 17025:2005 Calibration Laboratory Accredited by (A2LA) American Association for Laboratory Accreditation, Certificate No. 1750.01.

Control Company is ISO 9001:2008 Quality Certified by DNV GL, Certificate No. CERT-01805-2006-AQ-HOU-RvA.

International Laboratory Accreditation Cooperation (ILAC) - Multilateral Recognition Arrangement (MRA).